

Axial Disc Double Check Valve



- PN16 Rated
- – 10°C to 120°C
- Flanged PN16
- Anti Hammer
- Excellent Value



Description

2 x Axial Disc Check Valve with a Cast Iron Body, EPDM Seat, Stainless Steel Spring, to suit PN16 Flanges, Rated PN16, Temperature -10°C to 120°C. Pumping and water distribution industry's.



Beschreibung

2 x Prüfen Axial Disc Ventil mit einem Gusseisenkörper , EPDM Sitz, Edelstahl-Feder, PN16 Flansche, bewertet PN16 zu entsprechen , Temperatur -10°C bis 120°C. Pumpen und Wasserversorgung der Industrie .



Descripción

2 x Axial del disco válvula de retención con un Cuerpo de hierro fundido , Asiento EPDM , resorte del acero inoxidable , para adaptarse a PN16 Bidas PN16 , Calificación , Temperatura de -10°C a 120°C. El bombeo y la industria de distribución de agua .



Description

2 x Axial Disc Check Valve avec un Cast Iron Body , EPDM Siège , Ressort en acier inoxydable , en fonction de PN16 Brides , Évalué PN16 , Température -10°C à 120°C . Pompage et de l'industrie de la distribution de l'eau de .

Description:

Our Axial Double Disc Check valve assembly is designed to protect drinking water against polluted water. It offers silent operation with exceptional robustness, very low head loss and excellent, reliable double sealing. Cast Iron body with anti corrosion epoxy coated internal and external paint. PN16 rated with EPDM seats and stainless steel spring. WRAS EPDM Gasket.

**Constructed from WRAS
Approved Components**

[View Product Online](#)

[Click
Here](#)

Axial Disc Double Check Valve Assembly Using CV5183 x 2

Pressure / Temperature Specifications

Pressure	PN16
Temperature	- 10°C to +120°C

- Completely guided disc on both top and bottom
- Perfect tightness, soft sealed even at low differential pressure.
- Spring automatically closes the disc at Zero flow, before flow reversal.
- Prevents Surge and water hammer.

Materials

Body	Cast Iron GG25
Seat	Cast Iron GG25
Disc	Cast Iron GG25
Disc Ring	EPDM
Spring	Stainless Steel
Bushing	Bronze
Stem	Stainless Steel
Bracket	Cast Iron GG25
Screw	stainless Steel
Gasket	WRAS Approved EPDM
Fixing Bolts/Nuts	BZP

Dimensions

DN	A	L	D	Kg
2"	97	200	165	17.5
2 1/2"	125	240	185	21.5
3"	150	280	200	27.5
4"	187	340	220	37.5
5"	220	400	250	54
6"	260	460	285	74
8"	340	576	340	126
10	420	708	405	160
12"	490	820	460	250

