



1

Pneumatic - Spring	3/2	Ordering code 212.11.1	5/2	Pneumatic - Spring
 		T TYPE 32 = 3 ways 52 = 5 ways	 	
		Weight gr. 1110 Minimum piloting pressure 2,5 bar		

Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"

Pneumatic - Differential external	3/2	Ordering code 212.11.12	5/2	Pneumatic - Differential external
 		T TYPE 32 = 3 ways 52 = 5 ways	 	
		Weight gr. 1380 Minimum piloting pressure 2,5 bar		

Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"

Pneumatic - Pneumatic	3/2	Ordering code 212.11.11	5/2	Pneumatic - Pneumatic
 		T TYPE 32 = 3 ways 52 = 5 ways	 	
		Weight gr. 1350 Minimum piloting pressure 2 bar		


Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"




Pneumatic - Pneumatic

5/3

Ordering code
212.53.1.11.11
FUNCTION
F 31 = Closed centres 32 = Open centres 33 = Pressured centres



Weight gr. 1650
Minimum piloting pressure 3 bar



Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air		10 bar	Min. -5°C				

