

<b>Sensitive pushbutton Ø30 - differential</b>	3/2	<b>Ordering code</b> <b>228.1.6.13/C</b>	5/2	<b>Sensitive pushbutton Ø30 - differential</b>		
Weight gr. 197 Operating force 18,5N (at 6 bar)				Weight gr. 217 Operating force 18,5N (at 6 bar)		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"

<b>Push button - Spring</b>	3/2	<b>Ordering code</b> <b>228.1.6.22/C</b>	5/2	<b>Push button - Spring</b>		
Weight gr. 225 Operating force 33N				Weight gr. 245 Operating force 33N		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"

<b>Raised pushbutton Ø22 - Spring</b>	3/2	<b>Ordering code</b> <b>228.1.6.23/C</b>	5/2	<b>Raised pushbutton Ø22 - Spring</b>		
Weight gr. 230 Operating force 33N				Weight gr. 250 Operating force 33N		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	540 NI/min	mm 6	G 1/8"