



Compact Single Steam Trapping Station

- Simple Trap Installation in Minutes
- Compact and Reliable
- Body: Cast Stainless Steel
- Fits most Steam Traps
- Sizes:- ½", ¾" & 1"
- Fitted with Strainer and NRV

> Description

The New TLV Single Steam Trapping Station, each has a strainer fitted which prevents equipment damage from particles and rust, commonly found in pipelines, it also has a Non Return Valve (Check) that prevents backflow. Equipped with an upstream and downstream lockable isolation valve. The trapping station accommodates steam traps for condensate drainage for a wide range of applications, including process use and steam mains. The main use of this unit is for safe and quick trap removal and replacement in minutes. The universal 2 bolt connector allows float and thermodynamic steam traps to be fitted. Because the mounting is universal, this allows not just TLV to be installed, but other trap manufacturers units.

- Sizes offered are ½", ¾" and 1"
- Maximum Pressure 10 Bar
- Maximum Temperature 185°C

For more technical information see manufacturers data.

Can also be supplied with double upstream/down stream isolation, multiple piping arrangements and optional blowdown valve. (Please speak to our sales team).



Description

The new TLV Steam Trapping Station offers safe and quick maintenance on steam mains and process use. Offered in sizes from DN15-DN25 (G½"-G1"). Universal trap base plate (2 x bolt) for quick removal and replacement of traps. Single isolation on both up and down steam flows, check valve and strainer included. 10 Bar rated at 185°C.



Beschreibung

Die neue TLV Steam Trapping Station bietet eine sichere und schnelle Wartung von Dampfleitungen und Prozessanwendungen. Erhältlich in Größen von DN15-DN25 (G½"-G1"). Universelle Ableiter-Grundplatte (2 x Bolzen) zum schnellen Entfernen und Austauschen von Ableitern. Einzelabsperrung für Aufwärts- und Abwärtsdampfströme, Rückschlagventil und Sieb inklusive. 10 Bar bei 185°C bewertet.









Descripción

La nueva estación de trampas de vapor de TLV ofrece un mantenimiento seguro y rápido en las tuberías principales de vapor y el uso del proceso. Se ofrece en tamaños desde DN15-DN25 (G½"-G1"). Placa base de trampa universal (2 pernos) para retirar y reemplazar rápidamente las trampas. Aislamiento único en los flujos de vapor ascendentes y descendentes, válvula de retención y filtro incluidos. 10 bar clasificado a 185°C.



Description

La nouvelle station de purge de vapeur TLV offre une maintenance sûre et rapide sur les conduites de vapeur et l'utilisation du processus. Proposé dans les tailles DN15-DN25 (G½"-G1"). Plaque de base du purgeur universelle (2 x boulons) pour un retrait et un remplacement rapides des purgeurs. Isolation unique sur les flux de vapeur ascendants et descendants, clapet anti-retour et crépine inclus. 10 Bar évalué à 185°C.

Model	J32-X	S1(N)	S3	L21	P46UC
Steam Trap Type	Free Float	Free Float	Free Float	Thermostatic	Thermodynamic
PMO (Bar)	32	21	21	21	46
TMO °C	240	220	400	235	425
Max. discharge capacity (kg/h)	670	200	215	760	740
Trap Image					
Accommodates Spirax Steam Trap	UFT14 	UTD30H 	UBP30/32 		
Accommodates ARI Steam Trap	CONA S Ball Float 	CONA TD Thermodynamic 	CONA M Thermostatic 	CONA B Bimetallic 	

All information is sourced from our manufacturer's data and is intended for guidance only - Valves Online can accept no liability for changes, omissions or errors.

